



**Part Number:** 1031A

300V, (1 triad) 16 AWG (7x24) BC, PVC/PVC, Foil Shld, PLTC-ER, CMG

## Product Description

One 16 AWG triad stranded (7x24) bare copper conductors, twisted triads, PVC insulation, overall Beldfoil® shield (100% coverage), PVC jacket.

## Product Specifications

## Technical Specifications

### Construction and Dimensions

#### Conductor:

AWG	Stranding	Material	No. of Conductors	No. of Triads
16	7x24	BC - Bare Copper	1	1
<b>Total Number of Conductors:</b>			3	

#### Insulation:

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.016 in

#### Color Chart 2:

Number	Number
1	Black & Red & White and Numbered

#### Stranding:

Twists
6 twist/ft

## Outershield 1:

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum Foil-Polyester Tape	Beldfoil®	100 %	TC - Tinned Copper	18	7x26 mm

## Outerjacket 1:

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord
PVC - Polyvinyl Chloride	0.271 in	0.037 in	Yes

<b>Print Legend:</b>	LEGEND: BELDEN 1031A E34972 1TRD16 SHIELDED (UL) CMG 105C OR PLTC OR ITC SUN RES OR AWM 2464 80C 300V OR C(UL) CMG ---FT4 IEEE 1202 (2 FT, 7 DIGIT SEQUENTIAL NUMBER) FEET
----------------------	--

## Electrical Characteristics

### Conductor DCR:

Nominal Conductor DCR	Nominal Outer Shield DCR
3.7 Ohm/1000ft	4.9 Ohm/1000ft

### Capacitance:

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
54.1 pF/ft	97.3 pF/ft

### Inductance:

Nominal Inductance
0.156 µH/ft

### Voltage:

UL Voltage Rating
300 V RMS

## Use

Suitability - Burial:	Yes
Suitability - Sunlight Resistance:	Yes
Max Recommended Pulling Tension:	61 lbs

## Safety

CSA Flammability:	FT4
IEEE Flammability:	1202
UL Flammability:	UL1685 FT4 Loading

## Temperature Range

Operating Temp Range:	-30°C To +105°C
-----------------------	-----------------

## Mechanical Characteristics

Min Bend Radius/Minor Axis:	2.7 in
-----------------------------	--------

## Part Number

Plenum (Y/N):	No
---------------	----

## Standards

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)
CEC/C(UL) Specification:	CEC/C(UL) Specification
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)
NEC/(UL) Specification:	NEC/(UL) Specification
UL AWM Style:	AWM Specification
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	EU CE Mark

## History

Notes:	Alternate color coding available upon request.
--------	--

## Product Variants

Part Number	Color	Put-Up Type	Length
1031A 00610000	BLUE, LIGHT	Reel	10000 ft
1031A 0061000	BLUE, LIGHT	Reel	1000 ft
1031A 01010000	BLACK	Reel	10000 ft
1031A 0101000	BLACK	Reel	1000 ft
1031A 0105000	BLACK	Reel	5000 ft

© 2016 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

